



## BIGCHO 2 WATERER

### BIGCho 2 24V/50W or 80W

Frost-free non-spill stainless steel waterer with constant level, to be mounted on stand

Easy installation: 6 mounting positions. Largely proportioned bowl for installation between 2 pens.



8 l/min. at 3 bars

Stainless steel bowl and cover



Metal anti-spillage edge.

Double skin H.D.P.E. base, insulated by polyurethane foam.



#### Technical characteristics:

- bowl depth : 100 mm
- capacity : 5,5 litres
- to be mounted on PE or concrete stands (int Ø 300 mm).
- trough height: 560 mm on 400 mm PE stand, 760 mm on 600 mm PE stand, 900 mm on 740 mm PE stand
- Stainless steel screwed drain plug, ½" stainless steel braided hose and drain hose included.
- Transformer 230/24 V required, delivered separately.



Frost-free electrical system effective up to -20°C. : resistance 24 V/50 or 80 w.  
Also exists in non frost-free version.

Description
Frost-free 24 V - 50 W non-spill stainless steel waterer with constant level
Ditto precedent with frost-free 24 V - 80 W ( for Nordic countries)
No frost-free system

### ACCESSORIES



Transformers (230/24V)  
Shelltype European norm EN 60.742.

Description
Transformer 50 VA for 1 LAKCHO 50W
Transformer 100 VA for 2 LAKCHO 50W or 1 ISOBAC 100W or equivalent 100W
Transformer 200 VA for 4 LAKCHO 50W or 2 ISOBAC 100W or equivalent 200W
Transformer 300 VA for 6 LAKCHO 50W or 3 ISOBAC 100W or equivalent 300W
Transformer 400 VA for 8 LAKCHO 50W or 4 ISOBAC 100W or equivalent 400W
Remote thermostat for frost-free electric waterers: Automatic on/off according to the temperature (3°C / 37.4°F). Watertight cabinet. Max capacity: 1200 W

### PU FOAM INSULATED STANDS

polyethylene stands insulated by polyurethane foam

With a hole for drain hose, insulating plug included.



**H 400 mm:**  
Model especially designed for little animals: calves, sheeps, Non-contractual goats, ponies

**H 600 mm:**  
Model designed for for cattle in the existing buildings.

**H 740 mm:**  
Model especially designed for horses.

**H 1000 mm:**  
Model designed for cattle, in new buildings.



Description
1000 mm high to be embedded in 400 mm concrete
740 mm high, to be fixed on the floor, 4 points., especially designed for horses
600 mm high, to be fixed on the floor.
400 mm high, to be fixed on the floor, especially designed for little animals: calves, sheeps, goats, ponies...